

FEUILLES SBR

 -10°C +70°C


CARACTERISTIQUES

Feuilles en SBR
 Dureté : ± 65 ShA
 Densité : 1,6 + 5%
 Résistance à la traction : 65 kg/cm² + 5%
 Allongement à la rupture : 300%
 Modèle de tapis caoutchouc polyvalent



SANS PLI - COLORIS : NOIR

Epaisseur (mm)	Dimensions (m)	Code	Prix (€/m ²)
1	1,40 x 10	TAPLI0P14000114	
1,5	1,40 x 10	TAPLI0P140001514	
2	1,40 x 10	TAPLI0P14000214	
3	1,40 x 10	TAPLI0P14000314	
4	1,40 x 10	TAPLI0P14000414	
5	1,40 x 10	TAPLI0P14000514	
6	1,40 x 10	TAPLI0P14000614	
8	1,40 x 5	TAPLI0P14000807	
10	1,40 x 5	TAPLI0P14001007	
15	1,40 x 5	TAPLI0P14001507	
20	1,00 x 1	TAPLI0P10002001	
30	1,00 x 1	TAPLI0P10003001	
40	1,00 x 1	TAPLI0P10004001	
50	1,00 x 1	TAPLI0P10005001	

1 PLI - COLORIS : NOIR

Epaisseur (mm)	Dimensions (m)	Code	Prix (€/m ²)
2	1,40 x 10	TAPLI1P14000214	
3	1,40 x 10	TAPLI1P14000314	
4	1,40 x 10	TAPLI1P14000414	
5	1,40 x 10	TAPLI1P14000514	
6	1,40 x 10	TAPLI1P14000614	
8	1,40 x 5	TAPLI1P14000807	
10	1,40 x 5	TAPLI1P14001007	

2 PLIS - COLORIS : NOIR

Epaisseur (mm)	Dimensions (m)	Code	Prix (€/m ²)
3	1,40 x 10	TAPLI2P14000314	
4	1,40 x 10	TAPLI2P14000414	
5	1,40 x 10	TAPLI2P14000514	
6	1,40 x 10	TAPLI2P14000614	
8	1,40 x 5	TAPLI2P14000807	
10	1,40 x 5	TAPLI2P14001007	
15	1,40 x 5	TAPLI2P14001507	